

No image
available

TWISTER Series

TWISTER W/GRIP 52MM STORZ

DS1040P52MM

10&40 GPM DUAL GALLONAGE

\$305.00 List Price

FEATURES

Dual gallonage nozzle with two flow settings of 10 and 24 gpm @ 100 psi (37 and 90 l/min @ 7 bar). All lightweight materials, hard coat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. Rocker lug 1" NH (25mm) swivel is standard.

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	10/40 gpm (37/150 l/min)
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	2.7
Bumper Material	Rubber - press fit

DOCUMENTS

Service Procedures

[1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

[1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

[C1024 ITEM SPECIFICATION \(DOC\)](#)

[PARTS LIST: D SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

[PARTS LIST: F SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[Z SPANISH MANUAL: BOQUILLAS TWISTER® AND BUBBLECUP® \(PDF\)](#)

ABOUT THE TWISTER SERIES

A selectable, dual gallonage, combination nozzle available in ¾" (19mm), 1" (25mm) and 1.5" (38mm) threads and is designed for simplicity and durability. The rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, and high flow fog. The rugged, economical nozzle also accepts the FoamJet multi-expansion foam aspirating attachment.