



TWISTER Series

TWISTER TIP 1.5\"F

F2095

20&95 GPM DUAL GALLONAGE

\$171.00 List Price

FEATURES

Dual gallonage nozzle with two flow settings of 20 and 95 gpm @ 100 psi (75 and 360 l/min @ 7 bar). All lightweight materials, hard coat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1.5" NH (38mm) rigid thread is standard.

SPECIFICATIONS

Pistol Grip	No
Valve Design	Twist Style Baffle
Flow Rate	20/95 gpm (75/360 l/min)
Break Apart Style	Tip Only
Inlet Coupling Style	Knurled
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Rigid
Style	Break-Apart
Pressure Mode	Single
Type	Selectable
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	1.2
Bumper Material	Rubber - press fit

DOCUMENTS

Service Procedures

[1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

[1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

[C1024 ITEM SPECIFICATION \(DOC\)](#)

[F2095 FINISHED GOOD PRINT \(PDF\)](#)

[F2095 FINISHED GOOD PRINT - STEP \(DXF\)](#)

[F2095 ITEM SPECIFICATION \(DOC\)](#)

[PARTS LIST: D SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

[PARTS LIST: F SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[Z SPANISH MANUAL: BOQUILLAS TWISTER® AND BUBBLECUP® \(PDF\)](#)

ABOUT THE TWISTER SERIES

A selectable, dual gallonage, combination nozzle available in ¾" (19mm), 1" (25mm) and 1.5" (38mm) threads and is designed for simplicity and durability. The rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, and high flow fog. The rugged, economical nozzle also accepts the FoamJet multi-expansion foam aspirating attachment.