



QUADRAFOG Series

QUADRAFOG W/GRIP 1.5\"/>

FQS125PS

30-125 GPM @ 100 PSI SPINNING TEETH

\$1010.00 List Price

FEATURES

Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110-230-360-470 l/min @ 7bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1.5\"/>

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	30/60/95/125gpm (110/230/360/470 l/min)
Inlet Coupling Style	Rocker
Body Size	1.5\" (38 mm)
Inlet Coupling Swivel	Non-Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Fog Teeth	Spinning
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	3.75
Bumper Material	Rubber - bonded
Certification	NFPA/FM

DOCUMENTS

Service Procedures

[QUADRAFOG SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

[FQS125PS FINISHED GOOD PRINT \(PDF\)](#)

[FQS125PS FINISHED GOOD PRINT \(ZIP\)](#)

[FQS125PS FINISHED GOOD PRINT - STEP \(DXF\)](#)

[FQS125PS ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

[Z FRENCH MANUEL: THUNDERFOG, QUADRAFOG AND QUADRACUP \(PDF\)](#)

Online Videos

[QUADRAFOG SERIES VIDEO \(MP4\)](#)

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)

Certifications & Approvals

[QUADRAFOG 1000 \(QF1000-SL\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

[QUADRAFOG 150 PN40 EN15182-4 \(PDF\)](#)

ABOUT THE QUADRAFOG SERIES

An excellent selectable gallonage nozzle for any 1\"/>