



SMOOTHBORE Series

STRAIGHT TIP 1-1/8" X 1.5"F

FSS10

NH THREAD

\$120.00 List Price

FEATURES

with smooth inside taper. 1.5" NH (38mm) thread is standard.

*Please specify model # and orifice when ordering.

SPECIFICATIONS

Pistol Grip	No
Inlet Coupling Style	Knurled
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Rigid
Type	Smoothbore
Remote Control	No
Weight	1

DOCUMENTS

Technical Specifications and Drawings

[FSS10 ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[SMOOTH BORE / VIT INSERTS KIT \(PDF\)](#)

Product Brochures

[SMOOTH BORE SERIES FIXED FLOW ATTACK \(PDF\)](#)

ABOUT THE SMOOTHBORE SERIES

Engineered with a smooth, tapered waterway, TFT's smooth bore tips provide the stream quality, reach, and penetration that you have come to expect from a traditional smooth bore. Engineered for performance and durability, all smooth bore tips are manufactured from aluminum alloy which is then hard coat anodized, the critical orifice of the smooth bore is recessed 1/8" back into the taper, and an aluminum bumper is machined around the outside of that same edge to prevent damage to the critical orifice edge. The smooth bore size and an easy to read pressure/flow chart is laser engraved on each smooth bore tip to identify which smooth bore will meet your tactical needs on the fireground.