


THUNDERFOG Series
THUNDERFOG W/GRIP 1.5\"/>
FTS200PS

30-200 GPM @ 100 PSI SPINNING TEETH

\$1185.00 List Price
FEATURES

Selectable gallonage nozzle with six flow settings of 30, 60, 95, 125, 150, and 200 gpm @ 100 psi (110-230-360-470-570-750 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1.5\"/>

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	30/60/95/125/150/200gpm
Inlet Coupling Style	Rocker
Body Size	1.5\"/>
Inlet Coupling Swivel	Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Fog Teeth	Spinning
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	6.5
Bumper Material	Rubber - bonded
Certification	NFPA/FM

DOCUMENTS

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)
[Z INDONESIAN THUNDERFOG \(PDF\)](#)

Technical Specifications and Drawings

[FTS200PS FINISHED GOOD PRINT \(PDF\)](#)
[FTS200PS FINISHED GOOD PRINT \(ZIP\)](#)
[FTS200PS FINISHED GOOD PRINT - STEP \(DXF\)](#)
[FTS200PS ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

Online Videos

[THUNDERFOG SERIES VIDEO \(MP4\)](#)

ABOUT THE THUNDERFOG SERIES

A selectable gpm nozzle that is available in two basic series: the 200 series, with a selectable flow range of 30-200 gpm (110-750 l/min), or 95-250gpm (360-950 l/min) and the 250 series, with a selectable flow range of 95-250 gpm (360-950 l/min). The 200 series is an excellent choice for 1.5\", 1.75\", or 2.0\"/>