


G-FORCE Series
**G-FORCE 1.5'F VALVE W/GRIP
GF3A1S**

FIXED 150 GPM @ 100 PSI SPINNING TEETH

\$714.00 Guaranteed US Price
FEATURES
SPECIFICATIONS

Pistol Grip	Yes
Flow Rate	150 gpm (565 l/min)
Inlet Coupling Style	Rocker
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Full-Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Fixed
Fog Teeth	Spinning
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	4.4
Bumper Material	Rubber - bonded
Certification	NFPA/FM
Inlet Connection Type	NH Female

DOCUMENTS

Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)
[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)
[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)
[IMPULSE™ TRIGGER VALVE SYSTEM MAINTENANCE AND SERVICE PROCEDURE \(PDF\)](#)

Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

Product Catalogs

[G-FORCE CATALOG \(PDF\)](#)
[G-FORCE SPANISH CATALOG \(PDF\)](#)
[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)
[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)
[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)
[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)
[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

Certifications & Approvals

[G-FORCE \(GP**V**\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)
ABOUT THE G-FORCE SERIES

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.