

No image available

**G-FORCE Series**
**G-FORCE 1.5" F TIP/VALVE**
**GF5C1F**

SEL 30/60/95/125/150 GPM @ 100 PSI FIXED FOG TEETH

**\$714.00 Guaranteed US Price**
**FEATURES**
**SPECIFICATIONS**

<b>Pistol Grip</b>	No
<b>Break Apart Size</b>	1.5" x 1.5"
<b>Flow Rate</b>	30/60/95/125/150gpm (110/230/360/470/570 l/min)
<b>Break Apart Style</b>	Ball Valve
<b>Inlet Coupling Style</b>	Rocker
<b>Body Size</b>	1.5" (38 mm)
<b>Inlet Coupling Swivel</b>	Full-Time Swivel
<b>Style</b>	Break-Apart
<b>Pressure Mode</b>	Single
<b>Type</b>	Selectable
<b>Fog Teeth</b>	Fixed
<b>Operating Pressure</b>	100 psi (7 bar)
<b>Remote Control</b>	No
<b>Weight</b>	5.6
<b>Bumper Material</b>	Rubber - bonded
<b>Inlet Connection Type</b>	NH Female
<b>Package</b>	Yes

**DOCUMENTS**

## Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)
[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)
[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)
[IMPULSE™ TRIGGER VALVE SYSTEM MAINTENANCE AND SERVICE PROCEDURE \(PDF\)](#)

## Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

## Product Catalogs

[G-FORCE CATALOG \(PDF\)](#)
[G-FORCE SPANISH CATALOG \(PDF\)](#)
[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)
[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

## Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)
[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)
[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)
[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

## Certifications &amp; Approvals

[G-FORCE \(GP\\*\\*V\\*\\*\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

## **ABOUT THE G-FORCE SERIES**

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.