


G-FORCE Series
**G-FORCE 1.5 BSPF VALVE
W/GRIP**
GPB3Y2M

SEL 100/200/300/400/500 LPM AT 6BAR

\$575.00 Guaranteed US Price
FEATURES
SPECIFICATIONS

| | |
|------------------------------|---------------------------|
| Pistol Grip | Yes |
| Flow Rate | 100/200/300/400/500 l/min |
| Inlet Coupling Style | Knurled |
| Body Size | 1.5" (38 mm) |
| Inlet Coupling Swivel | Full-Time Swivel |
| Style | One Piece with Valve |
| Pressure Mode | Single |
| Type | Selectable |
| Fog Teeth | Fixed |
| Operating Pressure | 6 bar (87psi) |
| Remote Control | No |
| Weight | 4.8 |
| Bumper Material | Rubber - bonded |
| Certification | EN |
| Inlet Connection Type | BSP Female |

DOCUMENTS

Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)
[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)
[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)

Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

Product Catalogs

[G-FORCE SPANISH CATALOG \(PDF\)](#)
[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)
[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)
[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)
[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)
[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

Certifications & Approvals

[G-FORCE \(GP**Y**\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)
ABOUT THE G-FORCE SERIES

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.