

No image  
available

**MASTERSTREAM Series**
**MASTERSTREAM 1000 ER  
W/PLUG 2.5"NH FLUSH**
**M-FAEP1000NJ**

12-24VDC - 300-1000 GPM @ 100 PSI AUTO

**\$2260.00 List Price**
**FEATURES**

Flow range of 300-1000 gpm (1100-3800 l/min). The automatic series features TFT's exclusive pressure adjustment knob. With a twist of the large knob on the front of the nozzle, constant operating pressure can be immediately adjusted to tactile detent settings between 80 and 120 psi (5.5 and 8.3 bar). At pressures other than 100 psi, maximum flow is determined by K-factor of 125. This design allows the user to flush the nozzle without shutting down flow to the nozzle. 2.5" NH (65mm) rocker lug swivel coupling is standard. 3.0" NH (75mm) or 3.5" NH (90mm) couplings optional. For use on TFT RC monitors only.

**SPECIFICATIONS**

<b>Valve Design</b>	No Valve
<b>Flow Rate</b>	300-1000 gpm (1100-3800 l/min)
<b>Inlet Coupling Style</b>	2.5"NH Female
<b>Inlet Coupling Swivel</b>	Non-Full Time Swivel
<b>Pressure Mode</b>	Adjustable
<b>Type</b>	Automatic
<b>Operating Pressure</b>	80-120psi (5.5-8.3bar)
<b>Remote Control</b>	Yes
<b>Weight</b>	15.35
<b>Bumper Material</b>	Metal - aluminum
<b>Certification</b>	CE

**DOCUMENTS**

Technical Bulletins &amp; Testing Reports

[NOZZLE TRAJECTORY ELEVATION FACTORS \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[MASTER STREAM FINAL ASSEMBLY \(PDF\)](#)
[MASTER STREAM NOZZLES AUTOMATIC AND SELECTABLE \(PDF\)](#)
[MASTER STREAM WITH FLUSH NOZZLE SERIES \(PDF\)](#)
[MASTERSTREAM 4000 ER AUTOMATIC AND SELECTABLE NOZZLES MANUAL \(PDF\)](#)
[Z FRENCH MANUEL : LANCES DE SÉRIE MASTERSTREAM](#)
[Z POLISH MASTER STREAM NOZZLES AUTOMATIC AND SELECTABLE](#)
[Z POLISH MASTER STREAM 3200 \(PDF\)](#)

Technical Specifications and Drawings

[M-FAEP1000NJ ITEM SPECIFICATION \(DOC\)](#)

Service Procedures

[PARTS LIST: MASTER 4000 AUTOMATIC \(PDF\)](#)
[PARTS LIST: MASTER 4000 SELECTABLE \(PDF\)](#)

## **ABOUT THE MASTERSTREAM SERIES**

The series offers a wide range of superior flow performance. 150-1000 gpm, 300 – 1250 gpm, 300-2000 gpm, and 600 – 4000 gpm ranges are readily available based upon firefighting needs. Manual and electronic remote nozzles are available.

### **Master Stream 1000 Series**

Adjustable from straight stream to a dense fog pattern with a flow range of 150 gpm – 1000 gpm. Models are available with either automatic pressure control, selectable gpm with five gallonage settings, or factory ordered fixed gpm models. All Master Stream series nozzles are also suitable for use with foam and accept the FJ-LX-M FOAMJET low expansion air aspirating attachment.

### **Master Stream with FLUSH Series**

This model has the ability to produce an excellent hard-hitting stream at any flow from 300 gpm to 1250 gpm (1100 l/min to 4800 l/min). It's easily adjustable from a straight stream to a wide dense fog pattern and is standard with a rugged aluminum bumper with fixed fog teeth. The nozzle features a selector ring behind the shaper that allows flow selection or flushing the nozzle of debris without shutting down flow. The Master Stream 1250 with Flush is suitable for use with foam.

### **Master Stream 1250 – 2000 Series**

The series has the ability to produce an excellent hard-hitting stream at any volume from 300 gpm to 2000 gpm ( 1100 - 8000 l/min). It is adjustable from a straight stream to a dense fog pattern. These nozzle features TFT's exclusive pressure adjustment knob. With a twist of the large knob on the front of the nozzle, operating pressure can be immediately adjusted to tactile detent settings between 70 and 120 psi (4.8 and 8.3 bar). At pressures other than 100 psi, maximum flow is determined by K-factor of 150.

### **Large Flow Master Stream Series**

This series is the only variable pressure nozzle with a flow range of 600 - 4000 gpm (2400-16000 l/min). The Master Stream 4000 features a unique user selectable operating pressure control. The Master Stream 4000 can provide industrial users the highest flow and longest stream reach of any constant pressure, variable flow nozzle in the world. Similar to other automatic TFT nozzles, the Master Stream 4000 can maintain a constant pressure throughout its flow range. The operating nozzle pressure of the Master Stream 4000 is field adjustable.

An optional selectable nozzle is readily available with flow settings of 2500 & 5000 gpm (10000 & 20000 l/min) at 100 psi (8 bar).