



#### **OUADRAFOG Series**

# QUADRAFOG 150 W/GRIP GFR20

OF150-GFR

20-40-100-150 LPM @ 6BAR

\$795.00 List Price

#### **FEATURES**

Selectable gallonage nozzle with four flow settings of 5, 10, 24, and 40 gpm @ 100 psi (40-100-150-230 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1" NH swivel is standard.

### **SPECIFICATIONS**

Pistol Grip	Yes
Valve Design	Stainless
Flow Rate	20/40/100/150 I/min
Body Size	2.5" (65 mm)
Inlet Coupling Swivel	Non-Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Туре	Selectable
Operating Pressure	6 bar (87psi)
Remote Control	No
Weight	2.7
Bumper Material	Rubber - press fit
Certification	EN

### **DOCUMENTS**

Service Procedures

QUADRAFOG SERVICE PROCEDURE (PDF)

Instructions For Installation, Safe Operation and Maintenance QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL (PDF)

Z FRENCH MANUEL: THUNDERFOG, OUADRAFOG AND OUADRACUP (PDF)

Online Videos

QUADRAFOG SERIES VIDEO (MP4)

**Product Brochures** 

QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES (PDF)

**Certifications & Approvals** 

QUADRAFOG 1000 (QF1000-SL) PN 16 EN15182-2 TYPE3 (PDF)

QUADRAFOG 150 PN40 EN15182-4 (PDF)

Technical Specifications and Drawings QF150-GFR ITEM SPECIFICATION (DOC)

## **ABOUT THE QUADRAFOG SERIES**

An excellent selectable gallonage nozzle for any 1" (25mm) or 1.5" (38mm) hose line. The QUADRAFOG is an economical and lightweight combination nozzle suitable for use with low-expansion or multi-expansion foam attachments. 1" versions range are 5-40 gpm (20-150 l/min) or 5-60gpm (20-230 l/min). The 1.5" version has a range of 30-125 gpm (110-470 l/min), and is available in high (100 psi) or low-pressure (75 psi) versions with either a molded rubber bumper or stainless steel spinning fog teeth.