



QUADRAFOG Series

**QUADRAFOG 235 W/GRIP
1.0" BSPF HIGH PRESS**

QF235-HP

20-40-100-150-235 LPM @ 6 BAR

\$880.00 List Price

FEATURES

SPECIFICATIONS

Pistol Grip	No
Remote Control	No
Weight	2.6

DOCUMENTS

Service Procedures

[QUADRAFOG SERVICE PROCEDURE \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

[Z FRENCH QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

Online Videos

[QUADRAFOG SERIES VIDEO \(MP4\)](#)

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)

Technical Specifications and Drawings

[QF235-HP ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[QUADRAFOG 1000 \(QF1000-SL\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

[QUADRAFOG 150 PN40 EN15182-4 \(PDF\)](#)

ABOUT THE QUADRAFOG SERIES

An excellent selectable gallonage nozzle for any 1" (25mm) or 1.5" (38mm) hose line. The QUADRAFOG is an economical and lightweight combination nozzle suitable for use with low-expansion or multi-expansion foam attachments. 1" versions range are 5-40 gpm (20-150 l/min) or 5-60gpm (20-230 l/min). The 1.5" version has a range of 30-125 gpm (110-470 l/min), and is available in high(100 psi) or low-pressure(75 psi) versions with either a molded rubber bumper or stainless steel spinning fog teeth.