



QUADRAFOG Series

**QUADRAFOG 500 W/GRIP
1.5" BSPF**

QF500

100-500 LPM @ 6 BAR FLASHOVER

\$1010.00 List Price

FEATURES

Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110-230-360-470 l/min @ 7bar). All lightweight materials, hard coat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1.5" NH (38mm) swivel is standard. FM Approved

SPECIFICATIONS

Pistol Grip	Yes
Flow Rate	100-500 l/min
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Non-Full Time Swivel
Pressure Mode	Single
Type	Selectable
Operating Pressure	6 bar (87psi)
Remote Control	No
Weight	3.8

DOCUMENTS

Service Procedures

[QUADRAFOG SERVICE PROCEDURE \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

[Z FRENCH MANUEL: THUNDERFOG, QUADRAFOG AND QUADRACUP \(PDF\)](#)

Online Videos

[QUADRAFOG SERIES VIDEO \(MP4\)](#)

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)

Certifications & Approvals

[QUADRAFOG 1000 \(QF1000-SL\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

[QUADRAFOG 150 PN40 EN15182-4 \(PDF\)](#)

Technical Specifications and Drawings

[QF500 FINISHED GOOD PRINT \(PDF\)](#)

ABOUT THE QUADRAFOG SERIES

An excellent selectable gallonage nozzle for any 1" (25mm) or 1.5" (38mm) hose line. The QUADRAFOG is an economical and lightweight combination nozzle suitable for use with low-expansion or multi-expansion foam attachments. 1" versions range are 5-40 gpm (20-150 l/min) or 5-60gpm (20-230 l/min). The 1.5" version has a range of 30-125 gpm (110-470 l/min), and is available in high(100 psi) or low-pressure(75 psi) versions with either a molded rubber bumper or stainless steel spinning fog teeth.