



### EDUCTOR Series

## EDUCTOR 95 GPM 1.5"F X 1.5"M

UE-095-NF-02

W/1" MALE CAMLOCK .25% .5% 1% 3% 6%

**\$935.00 List Price**

### FEATURES

### SPECIFICATIONS

|                               |                   |
|-------------------------------|-------------------|
| <b>Flow Rate</b>              | 95gpm (360 l/min) |
| <b>Inlet</b>                  | 1.5" (38 mm)      |
| <b>Inlet Coupling Style</b>   | Rocker            |
| <b>Inlet Coupling Swivel</b>  | Full Time Swivel  |
| <b>Outlet</b>                 | 1.5" (38 mm)      |
| <b>Outlet Coupling Style</b>  | Male Threads      |
| <b>Outlet Coupling Swivel</b> | Rigid             |
| <b>Pressure</b>               | 200psi (14bar)    |
| <b>Weight</b>                 | 4.5               |

### DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance

[EDUCTOR - 350 SERIES: IN-LINE FOAM EDUCTOR \(PDF\)](#)

[EDUCTOR, IN-LINE FOAM EDUCTOR MANUAL \(PDF\)](#)

[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE \(PDF\)](#)

[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE](#)

[Z GERMAN INLINE ZUMISCHER SERIE 125](#)

[Z PORTUGUESE EDUCTOR MANUAL EDUTOR DE ESPUMA \(PDF\)](#)

[Z SPANISH EDUCTOR SERIE 125 EN LINEA \(PDF\)](#)

Technical Specifications and Drawings

[350 SERIES EDUCTOR EXPLODED VIEW \(PDF\)](#)

[UE-095-NF-02 ITEM SPECIFICATION \(DOC\)](#)

Technical Bulletins & Testing Reports

[PRODUCT BULLETIN MATERIAL CHANGE UE940 2.5" IN-LINE EDUCTOR FOAM PICK-UP HOSE \(PDF\)](#)

### ABOUT THE EDUCTOR SERIES

In line foam eductors have a metering head with an easy-to-read knob for use with Class A, B and AR-AFFF foam at a variety of percentages. The meter head is equipped with a unique back flush push-button for fast and easy cleaning right on the scene, and is secured to the eductor body with a rugged disconnect. All controls are easy to use with gloves. The eductors are made of hardcoat anodized aluminum for corrosion protection.

- 125 Eductor Series are available in 60, 95, or 125 gpm models and have foam percentage settings of .25 %, .5 %, 1 %, 3 %, & 6 % allowing use with Class A or B foams. Models allow you choose between an extra-large 36" pickup hose with stainless steel wand or direct truck connect pickup hose.
- 250 and 350 Eductor Series are 250 gpm and 350 gpm in line Foam eductors for use with Class A foam or Class B foam. A large 8' industrial grade, UV resistant pickup hose is ideal for use with high viscosity foams.