

No image
available

EDUCTOR Series
**EDUCTOR 125 GPM 52MM
STORZ X 52MM STORZ**

UE-125-SH-SH

W/36" HOSE .25% .5% 1% 3% 6%

\$935.00 List Price
FEATURES
SPECIFICATIONS

Flow Rate	125 gpm (475 l/min)
Inlet	1.5" (38 mm)
Inlet Coupling Swivel	Full Time Swivel
Outlet	1.5" (38 mm)
Outlet Coupling Swivel	Rigid
Pressure	200psi (14bar)
Weight	4

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance

[EDUCTOR - 350 SERIES: IN-LINE FOAM EDUCTOR \(PDF\)](#)
[EDUCTOR, IN-LINE FOAM EDUCTOR MANUAL \(PDF\)](#)
[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE \(PDF\)](#)
[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE](#)
[Z GERMAN INLINE ZUMISCHER SERIE 125](#)
[Z PORTUGUESE EDUCTOR MANUAL EDUTOR DE ESPUMA \(PDF\)](#)
[Z SPANISH EDUCTOR SERIE 125 EN LINEA \(PDF\)](#)

Technical Specifications and Drawings

[350 SERIES EDUCTOR EXPLODED VIEW \(PDF\)](#)

Technical Bulletins & Testing Reports

[PRODUCT BULLETIN MATERIAL CHANGE UE940 2.5" IN-LINE EDUCTOR
FOAM PICK-UP HOSE \(PDF\)](#)
ABOUT THE EDUCTOR SERIES

In line foam eductors have a metering head with an easy-to-read knob for use with Class A, B and AR-AFFF foam at a variety of percentages. The meter head is equipped with a unique back flush push-button for fast and easy cleaning right on the scene, and is secured to the eductor body with a rugged disconnect. All controls are easy to use with gloves. The eductors are made of hardcoat anodized aluminum for corrosion protection.

- 125 Eductor Series are available in 60, 95, or 125 gpm models and have foam percentage settings of .25%, .5%, 1%, 3%, & 6% allowing use with Class A or B foams. Models allow you choose between an extra-large 36" pickup hose with stainless steel wand or direct truck connect pickup hose.
- 250 and 350 Eductor Series are 250 gpm and 350 gpm in line Foam eductors for use with Class A foam or Class B foam. A large 8' industrial grade, UV resistant pickup hose is ideal for use with high viscosity foams.