CROSSFIRE Series

STOW-A-WAY BASE 4.0"BSPM

XPL-2BP

DOUBLE INLET 3500 LPM NO SAFETY VALVE

$2090.00 List Price

FEATURES

WITHOUT SAFE-TAK VALVE is supplied with either two clappered swivel inlets or with a single full-time swivel inlet. Includes a safety tie-down strap with attached storage cap. STOW-A-WAY 800 portable base is not equipped with SAFE-TAK™ "Flow Safety Valve." Maximum recommended flow with Stow-A-Way Base in portable mode is 800 gpm (3500 l/min). Order XF500-KIT Option $570.00 to add a flow safety valve. Weight of safety valve is 3.1 lb (1.4kg).

© 2021 Task Force Tips. All Rights Reserved.

SPECIFICATIONS

Coupling Size Side A	4" (100mm)
Coupling Size Side B	2.5" (65 mm)
Coupling Style Side A	Rocker
Finish	International Red
Horizontal Control	N/A
Horizontal Movementdegrees	N/A
Inlet	Portable Base Dual Inlet
Max Flow	800gpm (3,500 l/min)
Operation Energy Source	Manual
Oscillation	No
Outlet	Quick Connect Male
Package	No
Safety Shutoff	No
Valve Design	No Valve
Vertical Control	N/A
Vertical Movementdegrees	N/A
Weight	0
Safety Inlet	No

DOCUMENTS

Service Procedures

CROSSFIRE XF500-KIT & XP500-KIT INSTALLATION INSTRUCTIONS (PDF)
PARTS LIST: CROSSFIRE & SAFE-TAK 1250 (PDF)
PARTS LIST: CROSSFIRE & SAFE-TAK 1250 (PDF)

Instructions For Installation, Safe Operation and Maintenance

CROSSFIRE STORAGE BRACKET (PDF)
CROSSFIRE® MONITOR MANUAL (PDF)
MONITOR EXTENSION PIPE (PDF)
Z FRENCH MANUEL : CANON À EAU CROSSFIRE®
Z GERMAN CROSSFIRE® MONITOR MANUAL (PDF)
Z ITALIAN CROSSFIRE® MONITOR MANUAL (PDF)
Z POLISH CROSSFIRE® MONITOR MANUAL
Z SPANISH MONITOR CROSSFIRE (PDF)

Product Order Forms

CROSSFIRE COMBINATION PACKAGES ORDER FORM (PDF)

Online Videos

CROSSFIRE CUP SEAL REPLACEMENT (MP4)
CROSSFIRE SERIES VIDEO (MP4)
HOW TO UPGRADE A STANDARD BLITZFIRE TO AN OSCILLATING BLITZFIRE (MP4)

Technical Specifications and Drawings

MONITOR DRAWING AND PART LIST (PDF)
PARTS LIST: CROSSFIRE BRACKET (PDF)

Technical Bulletins & Testing Reports

CROSSFIRE® AND HURRICANE™ SHAFT SEAL CHANGE (PDF)
PRODUCT BULLETIN 3" AND 4" MONITOR FLANGE CONNECTION CHANGE (PDF)
PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL CHANGE (PDF)

Certifications & Approvals

CROSSFIRE WITH STOW-A-WAY BASE EN15767-1 (PDF)

ABOUT THE CROSSFIRE SERIES

The CROSSFIRE monitor is a unique master stream appliance that's lightweight, compact and incredibly versatile. It can be connected to either a portable base or a truck.

With a flow rating of 1250 gpm in portable operation, the TFT Crossfire monitor integrates the exclusive Safe-Tak safety shutoff system to prevent unintentional movement. The monitor's compact and lightweight design includes stainless spring steel legs with carbide tips for maximum stability, and a visual attachment indicator for additional security.

Connect to a truck with the adapters or a TFT Extend-A-Gun with XL outlet. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" (83mm) which lets the CROSSFIRE deliver up to 1250 gpm (4500 l/min) with low friction loss.

© 2021 Task Force Tips. All Rights Reserved.