

**BLITZFORCE Series**

**BLITZFORCE 2.5" BSPF X  
2.5" BSPM**

XXL112A

SWIVEL ROCKER X RIGID MALE

**\$2017.00 Guaranteed US Price**

**FEATURES**

The BlitzForce is one of Task Force Tips' innovative, lightweight, and highly versatile portable attack monitors. Rated up to 2000 l/min (500 gpm), BlitzForce integrates a low loss waterway with positive locking valve control, and a corrosion preventing anodized and powder coat finish. An exclusive high strength tie-down strap and carbide tipped folding legs offer extreme stability in varying fire environments. With an integral stream shaper for superior reach and penetration performance, the BlitzForce delivers a 20 degree side to side (40 degree total) and a 20 degree to 60 degree up and down range of stream motion. A five year warranty, stainless steel apparatus mounting bracket, and your choice of combination nozzle or stacked tips are standard.



## SPECIFICATIONS

<b>Coupling Size Side A</b>	2.5" (65 mm)
<b>Coupling Size Side B</b>	2.5" (65 mm)
<b>Coupling Style Side A</b>	Rocker
<b>Finish</b>	Stardust Silver
<b>Horizontal Control</b>	N/A
<b>Horizontal Movementdegrees</b>	20 left and right of center
<b>Inlet</b>	2.5"Rocker Lug
<b>Max Flow</b>	500 gpm (2,000 l/min)
<b>Operation Energy Source</b>	Manual
<b>Oscillation</b>	No
<b>Outlet</b>	2.5"BSP Male
<b>Package</b>	No
<b>Safety Shutoff</b>	No
<b>Valve Design</b>	Ball Valve (Delrin/Acetal)
<b>Vertical Control</b>	N/A
<b>Vertical Movementdegrees</b>	20 to 60 degrees above horizontal
<b>Weight</b>	15
<b>Safety Inlet</b>	No

## ABOUT THE BLITZFORCE SERIES

The BLITZFORCE is a highly versatile portable attack monitors. It's rated up to 500 gpm (1,890 l/min) and integrates a low loss waterway with positive locking valve control, and a corrosion resistant anodized and powder coated finish. An exclusive high strength tie-down strap and carbide tipped folding legs offer extreme stability in varying fire environments. With an integral stream shaper for superior reach and penetration performance, the BLITZFORCE delivers a 20 degree side to side (40 degree total) and a 20 degree to 60 degree up and down range of stream motion.

## DOCUMENTS

Service Procedures

[BLITZFORCE MOUNTING INSTRUCTIONS \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[BLITZFORCE PORTABLE MONITOR MANUAL \(PDF\)](#)

[Z FRENCH MANUEL : CANON À EAU PORTABLE BLITZFORCE \(PDF\)](#)

[Z SPANISH BLITZFORCE MANUAL: MONITOR PORTÁTIL BLITZFORCE \(PDF\)](#)

Technical Bulletins & Testing Reports

[BLITZFORCE TIE-OFF STRAP \(PDF\)](#)

[PRODUCT BULLETIN BLITZFORCE™ LABEL CHANGE \(PDF\)](#)

[PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL CHANGE \(PDF\)](#)

Technical Specifications and Drawings

[PARTS LIST: BLITZFORCE BRACKET \(PDF\)](#)