



EF1 Series

EF1 RC MONITOR COMBO PACKAGE

Y1C-71

EF1-BUBBLE CUP ER- BLUETOOTH CONTROL

\$7080.00 List Price

FEATURES

Rated to 200 gpm (750 l/min) with a maximum operating pressure of 200 psi (14 bar), the EF1 RC is a remotely controlled truck mounted monitor with electric remote control of rotation and elevation angle. The EF1 RC has an electronically operated 270° horizontal rotational travel, user installed travel limit stops, stainless steel worm gear drive, and grease zerk fittings for easy service and lubrication. The discharge elbow includes an integral stream straightener. The monitor is constructed of hardcoat anodized aluminum alloy and has a silver powder coat finish.

SPECIFICATIONS

Oscillation	No
Package	Yes
Remote Control	No
Weight	0

DOCUMENTS

Technical Specifications and Drawings

[EF1 EXPLODED VIEW \(PDF\)](#)

[Y1C-71 ITEM SPECIFICATION \(DOC\)](#)

[YE-LK12-KIT ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[EF1 RC MONITOR \(PDF\)](#)

[REMOTE CONTROL \(RC\) MONITOR ELECTRICAL CONTROLS MANUAL \(PDF\)](#)

Product Brochures

[EF1 RC PRODUCT BROCHURE \(PDF\)](#)

Online Videos

[EF1 SERIES VIDEO \(MP4\)](#)

ABOUT THE EF1 SERIES

The EF1 remotely controlled monitor is a great option for wildland and interface apparatus. At less than 13" (319mm) tall, the EF1 is an ideal forestry bumper turret. The EF1 is hard coated aluminum alloy which is then powder coated inside and out. All electronics are tightly contained in a sealed control box that is part of the monitor casting. Monitor wiring is reduced to a minimum and installs easily using a one plug connection.

The EF1 is TFT's most compact monitor but its large, efficient waterway is capable of flows up to 200 gpm (760 l/min).