


**MONSOON Series**
**MONSOON RC**
**Y4-E21A**

4" ANSI 150 X 3.5" M

**\$9325.00 List Price**
**FEATURES**
**SPECIFICATIONS**

<b>Apparatus</b>	Pumper
<b>Certification</b>	CE
<b>Finish</b>	Stardust Silver
<b>Horizontal Control</b>	3" Handwheel
<b>Horizontal Movementdegrees</b>	225 left and right
<b>Inlet</b>	4" ANSI 150
<b>Max Flow</b>	2,000 gpm (7,600 l/min)
<b>Operation Energy Source</b>	12/24 VDC
<b>Oscillation</b>	No
<b>Outlet</b>	3.5in (90mm) NH Male
<b>Remote Control</b>	Yes
<b>Valve Design</b>	No Valve
<b>Vertical Control</b>	3" Handwheel
<b>Vertical Movementdegrees</b>	-45 to 90
<b>Weight</b>	42.5

**DOCUMENTS**

Instructions For Installation, Safe Operation and Maintenance

[MONSOON MONITOR INSTRUCTION MANUAL \(PDF\)](#)
[REMOTE CONTROL \(RC\) MONITOR ELECTRICAL CONTROLS MANUAL \(PDF\)](#)
[Z PORTUGUESE MONSOON RC MONITOR \(PDF\)](#)
[Z SPANISH MANUAL MONITOR MONSOON Y MONSOON RC-SPANISH \(PDF\)](#)

Certifications &amp; Approvals

[RC MONITORS AND NOZZLES ATEX CERTIFICATE BRAZIL \(PDF\)](#)
[RC MONITORS AND NOZZLES ATEX CERTIFICATE EUROPE \(PDF\)](#)

Technical Specifications and Drawings

[MONSOON DRAWING & PARTS LIST \(PDF\)](#)
[Y4-E21A FINISHED GOOD PRINT \(PDF\)](#)
[Y4-E21A ITEM SPECIFICATION \(DOC\)](#)
[Y4-E21A ITEM SPECIFICATION \(DOC\)](#)

Technical Bulletins &amp; Testing Reports

[LEC-019 INTEGRATING CANBUS WITH TFT RC MONITORS \(PDF\)](#)

Online Videos

[MONSOON SERIES VIDEO \(MP4\)](#)

Product Brochures

[MONSOON MONITOR PAGE \(PDF\)](#)
**ABOUT THE MONSOON SERIES**

The MONSOON is available in a manual or electrically controlled model in two versions: up to 1250 gpm (4750 l/min) or up to 2000 gpm (7600 l/min). With a unique patented segmented waterway, the water makes very few turns as it travels through the monitor resulting in low friction loss and a far-reaching effective stream. There are RC models specifically for pumpers or aerial apparatus with a wide range of controller, nozzle and EXTEND-A-GUN options.