


MONSOON Series
**MONSOON TILLER/CRANK
AMERICAN RED**
Y4-T25A-Z

4.0"ANSI 150 X 2.5"M

\$3080.00 List Price
FEATURES
SPECIFICATIONS

Apparatus	Pumper
Certification	FM
Finish	American Red
Horizontal Control	Tiller Bar w/Lock
Horizontal Movementdegrees	Continuous 360
Inlet	4"ANSI 150
Max Flow	1,250 gpm (4,500 l/min)
Operation Energy Source	Manual
Oscillation	No
Outlet	2.5"NH Male
Remote Control	No
Valve Design	No Valve
Vertical Control	Alum Crank Handle
Vertical Movementdegrees	-45 to 90
Weight	30.2

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance

[MONSOON MONITOR INSTRUCTION MANUAL \(PDF\)](#)
[REMOTE CONTROL \(RC\) MONITOR ELECTRICAL CONTROLS MANUAL \(PDF\)](#)
[Z PORTUGUESE MONSOON RC MONITOR \(PDF\)](#)
[Z SPANISH MANUAL MONITOR MONSOON Y MONSOON RC-SPANISH \(PDF\)](#)

Certifications & Approvals

[RC MONITORS AND NOZZLES ATEX CERTIFICATE BRAZIL \(PDF\)](#)
[RC MONITORS AND NOZZLES ATEX CERTIFICATE EUROPE \(PDF\)](#)

Technical Bulletins & Testing Reports

[LEC-019 INTEGRATING CANBUS WITH TFT RC MONITORS \(PDF\)](#)

Online Videos

[MONSOON SERIES VIDEO \(MP4\)](#)

Product Brochures

[MONSOON MONITOR PAGE \(PDF\)](#)

Technical Specifications and Drawings

[MONSOON DRAWING & PARTS LIST \(PDF\)](#)
[Y4-T25A-Z ITEM SPECIFICATION \(DOC\)](#)
ABOUT THE MONSOON SERIES

The MONSOON is available in a manual or electrically controlled model in two versions: up to 1250 gpm (4750 l/min) or up to 2000 gpm (7600 l/min). With a unique patented segmented waterway, the water makes very few turns as it travels through the monitor resulting in low friction loss and a far- reaching effective stream. There are RC models specifically for pumpers or aerial apparatus with a wide range of controller, nozzle and EXTEND-A-GUN options.