

No image
available

TYPHOON Series

TYPHOON RC FOR LADDER NO ANTI-BD-GEARBOX

Y5-EB1A-L302

1.5" OFFSET 4.0" ANSI X 3.5" M 30 DEGREE

\$8925.00 List Price

FEATURES

SPECIFICATIONS

Apparatus	Aerial Ladders
Certification	CE
Finish	Stardust Silver
Horizontal Control	3" Handwheel
Horizontal Movementdegrees	90 left and right
Inlet	4" ANSI 150 with 1.5" offset
Max Flow	1,500 gpm (6,000 l/min)
Operation Energy Source	12/24 VDC
Oscillation	No
Outlet	3.5in (90mm) NH Male
Remote Control	Yes
Valve Design	No Valve
Vertical Control	3" Handwheel
Vertical Movementdegrees	45 below to 120 above horizontal
Weight	43.5

DOCUMENTS

Technical Specifications and Drawings

[TYPHOON EXPLODED VIEW AND PARTS LIST \(PDF\)](#)

[Y5-EB1A-L302 ITEM SPECIFICATION \(DOC\)](#)

[YE-LK12-KIT ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[RC MONITORS AND NOZZLES ATEX CERTIFICATE BRAZIL \(PDF\)](#)

[RC MONITORS AND NOZZLES ATEX CERTIFICATE EUROPE \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[TYPHOON & TYPHOON RC MONITOR INSTRUCTION MANUAL \(PDF\)](#)

[TYPHOON EXPLODED VIEW AND PARTS LIST \(PDF\)](#)

[Z PORTUGUESE TYPHOON RC MONITOR \(PDF\)](#)

Technical Bulletins & Testing Reports

[LEC-019 INTEGRATING CANBUS WITH TFT RC MONITORS \(PDF\)](#)

Service Procedures

[PARTS LIST: TYPHOON \(PDF\)](#)

ABOUT THE TYPHOON SERIES

The TYPHOON is available in a manual or electrically controlled models with flows up to 1500 gpm (6000 l/min). It's available with various inlet flanges and threaded fittings. Inlets are also made for direct connection to TFT's Extend-A-Gun series and Valve Under Monitor series. The waterway with turning vane has only 19 psi (1.3 bar) loss at 1500 gpm (6000 l/min). There are RC models specifically for pumpers or aerial apparatus with a wide range of controller, nozzle and EXTEND-A-GUN options.