



SMOOTHBORE Series

4 STACK TIPS 3.5" FEMALE

YST-4NN

2.75" 2.50" 2.25" 2.00" TIPS

\$1379.00 List Price

FEATURES

Designed for monitor use up to 2000 gpm (8000 l/min), these lightweight tips are hard coat anodized, allow four orifice options, have a built in stream straightener and pressure/flow charts laser engraved on each tip. Orifice openings are 2.75", 2.5", 2.25", and 2.0". (70mm, 65mm, 57mm and 50mm) 3.5" NH (89mm) swivel inlet coupling is standard.

SPECIFICATIONS

Inlet Coupling Style	Rocker
Body Size	3.5" (90mm)
Style	Smoothbore
Remote Control	No
Weight	10.7
Connection Type	NH Female
Coupling Size	3.5" (90mm)
Coupling Swivel	Full Time Swivel
Orifice Sizes	2.75"(70mm) 2.50" (65mm) 2.25"(57mm) 2.00" (50 mm)

DOCUMENTS

Flow & Reaction Charts

[STACKED TIPS YST-4NN FLOW & REACTION CHARTS \(PDF\)](#)

Technical Specifications and Drawings

[YST-4NN FINISHED GOOD PRINT \(PDF\)](#)

[YST-4NN FINISHED GOOD PRINT \(ZIP\)](#)

[YST-4NN FINISHED GOOD PRINT - STEP \(DXF\)](#)

[YST-4NN ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[SMOOTH BORE / VIT INSERTS KIT \(PDF\)](#)

Product Brochures

[SMOOTH BORE SERIES FIXED FLOW ATTACK \(PDF\)](#)

ABOUT THE SMOOTHBORE SERIES

Engineered with a smooth, tapered waterway, TFT's smooth bore tips provide the stream quality, reach, and penetration that you have come to expect from a traditional smooth bore. Engineered for performance and durability, all smooth bore tips are manufactured from aluminum alloy which is then hard coat anodized, the critical orifice of the smooth bore is recessed 1/8" back into the taper, and an aluminum bumper is machined around the outside of that same edge to prevent damage to the critical orifice edge. The smooth bore size and an easy to read pressure/flow chart is laser engraved on each smooth bore tip to identify which smooth bore will meet your tactical needs on the fireground.

Learn More: [Do you even need a firefighting nozzle?](#)