



**SMOOTHBORE Series**

**4 STACK TIPS 7" QUICK CONNECT**

**YST-8NX**

5.125" 4.50" 4.00" 3.50" TIPS

**\$3915.00 List Price**

**FEATURES**

Designed for monitor use up to 8000 gpm (30280 l/min), these stacked tips are hardcoat anodized, allow four orifice options, have a built in stream straightener and pressure/flow charts laser engraved on each tip. Orifice openings are 5.125", 4.5", 4.0", and 3.5". (130mm, 114mm, 102mm and 89mm). Quick connect inlet coupling for Tsunami monitor is standard.

**SPECIFICATIONS**

<b>Inlet Coupling Style</b>	Quick Connect
<b>Body Size</b>	7.0" (178mm)
<b>Style</b>	Smoothbore
<b>Remote Control</b>	No
<b>Weight</b>	37.7
<b>Connection Type</b>	Quick Connect
<b>Coupling Size</b>	7.0" (178mm)
<b>Coupling Swivel</b>	Rigid
<b>Orifice Sizes</b>	5.125"(130mm) 4.5" (114mm) 4.0"(102mm) 3.5" (89 mm)

**DOCUMENTS**

Instructions For Installation, Safe Operation and Maintenance  
[SMOOTH BORE / VIT INSERTS KIT \(PDF\)](#)

Product Brochures  
[SMOOTH BORE SERIES FIXED FLOW ATTACK \(PDF\)](#)

Technical Specifications and Drawings  
[YST-8NX FINISHED GOOD PRINT \(DXF\)](#)  
[YST-8NX ITEM SPECIFICATION \(DOC\)](#)

**ABOUT THE SMOOTHBORE SERIES**

Engineered with a smooth, tapered waterway, TFT's smooth bore tips provide the stream quality, reach, and penetration that you have come to expect from a traditional smooth bore. Engineered for performance and durability, all smooth bore tips are manufactured from aluminum alloy which is then hard coat anodized, the critical orifice of the smooth bore is recessed 1/8" back into the taper, and an aluminum bumper is machined around the outside of that same edge to prevent damage to the critical orifice edge. The smooth bore size and an easy to read pressure/flow chart is laser engraved on each smooth bore tip to identify which smooth bore will meet your tactical needs on the fireground.