No image available

iVUM (Industrial Valve Under Monitor) Series

IVUM ALUM 3.0"ANSI X 3.0"ANSI

ZAAD5-01

INTERNAL DRAIN/VALVE W/ADAPTER AA9FL-FP INSTALLED

$2045.00 List Price

FEATURES

SPECIFICATIONS

Drain	W/ Ball Drain
Finish	American Red
Gear Box Style	Shaft on Side
Inlet	3" ANSI
Inlet Flange	Aluminum
Operation Energy Source	Manual
Oscillation	No
Outlet	3" ANSI
Product	Industrial Valve Under Monitor (IVUM)
Remote Control	No
Valve Design	Ball Valve Aluminum
Weight	34.6

DOCUMENTS

Technical Specifications and Drawings

ZAAD5-01 ITEM SPECIFICATION (DOC)

Certifications & Approvals

INDUSTRIAL VALVE UNDER MONITOR FM APPROVAL (IVUM) (PDF)

ABOUT THE IVUM (INDUSTRIAL VALVE UNDER MONITOR) SERIES

The 4" Integrated Valve Under Monitor (IVUM) is a robust, low friction loss valve intended for installation directly beneath monitors on a fire protection riser or hydrant stem. The IVUM is built standard with 4" ANSI 150 or DN 100 PN16 flange connections.

All models are equipped with an external automatic drain valve to fully drain the monitor and valve body after use, thus minimizing susceptibility to damage from corrosion and freezing water. An optional internal automatic drain valve located within the half ball allows the standpipe to draw atmospheric air to facilitate draining, even while the half ball is closed. It is beneficial in applications where the standpipe will typically be drained following use, especially where freezing conditions are a concern.

Electrically controlled versions are available.

© 2021 Task Force Tips. All Rights Reserved.