

No image
available

Z Series

ZN INDUSTRIAL NOZZLE 2.5" BSPF

ZN24A

USER SPECIFIED K FACTOR 15-75

\$682.00 List Price

FEATURES

The Task Force Tips fixed gpm water nozzle is a simple and rugged industrial nozzle with superior stream quality and reach. This fixed gallonage fog nozzle rated at 100 psi (7 bar) is available with your choice of 350, 500, or 750 (1300, 2000, or 3000 l/min). fog angle is user adjustable between 120 degree wide fog and straight stream. The nozzle's baffle can be removed with a wrench for flushing debris. The standard inlet is 2.5" NH, NPSH, or BSP (65mm) female thread. The simple and basic design requires no grease or other maintenance. The rubber bumper is UV resistant. The fixed gpm water nozzle is Hardcoat anodized ANSI A356.0 T6 aluminum. The fixed gpm nozzle can be used with water or premixed foam solution

SPECIFICATIONS

Flow Rate	User Specified Kfactor
Inlet Coupling Style	Rocker
Inlet Coupling Swivel	Rigid
Type	Fixed
Operating Pressure	User Specified Kfactor
Remote Control	No
Weight	4.4
Bumper Material	Rubber - press fit

DOCUMENTS

Technical Specifications and Drawings

[PARTS LIST: ZM NOZZLE \(PDF\)](#)

[PARTS LIST: ZN NOZZLE \(PDF\)](#)

[PARTS LIST: ZO NOZZLE \(PDF\)](#)

[ZN24A ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[Z SERIES NOZZLES MANUAL \(PDF\)](#)

ABOUT THE Z SERIES

The Z series are fixed gpm water nozzles that are simple and rugged with superior stream quality and reach. The fog angle is user adjustable between 120 degree wide fog and straight stream. The simple and basic design requires no grease or other maintenance. This fixed gallonage fog nozzle family is rated at 100 psi (7 bar) is available with your choice of flow rates:

- ZN: 350, 500, or 750 (1300, 2000, or 3000 l/min)
- ZM: 500, 750, 1000, or 1250 (2000, 3000, 4000, or 4750 l/min)
- ZO: 1250, 1500, 1750, or 2000 (4750, 5500, 6750, or 7500 l/min)