

DETAIL AND SUBMITTAL SHEET

5000 Series - I	Hose Valves
Project/Location:	Date:
Architect/Engineer:	Qty:
Contractor:	
☑ Appropriate Selection	
Female v Male Angle Valves - Used as fire hose outlet connections	Female NPT inlet v Male hose thread

Female x Male Angle Valves - Used as fire hose outlet connections. Female NPT inlet x Male hose thread outlet, 300 PSI, cast brass, UL listed/FM approved

Model No.	Size	Α	B (Open)	С	D	Swing Radius
5010	1½" x 1½"	4"	73/4"	21/4"	2"	2½"
5015	2½" x 2½"	51/4"	11"	31/4"	23/4"	3½"

Optional Finish: ☐-B Polished Brass ☐-C Rough Chrome Plated ☐-D Polished Chrome Plated Threads: ☐NST ☐ Other _____

Female x Female Angle Valves - Used with hose rack assemblies. Female NPT inlet and outlet, 300 PSI, cast brass, UL listed/FM approved.

Model No.	Size	A	B (Open)	С	D	Swing Radius
5020	1½" x 1½"	4"	73/4"	21/4"	2"	21/2"
5025	2½" x 2½"	51/4"	11"	31/4"	23/4"	31/2"

Optional Finish: ☐-B Polished Brass ☐-C Rough Chrome Plated ☐-D Polished Chrome Plated

Female x Male Pressure Restricting Angle Valves - Used as fire hose outlet connections. Field-adjustable restricting mechanism reduces water pressure under flowing conditions (175 PSI max. inlet). When full flow is required, restriction can be over-ridden by trained personnel. Female NPT x Male hose thread outlet, 175 PSI, cast brass, UL listed/FM Approved.

Model No.	Size	Α	B (Open)	С	D	Swing Radius
5030	1½" x 1½"	4"	8"	21/4"	2"	2½"
☐ 5035	2½" x 2½"	51/4"	111/2"	31/4"	23/4"	3½"

Optional Finish: ☐-B Polished Brass ☐-C Rough Chrome Plated ☐-D Polished Chrome Plated Threads: ☐ NST ☐ Other _____

Female x Female Pressure Restricting Valves - Used with hose rack assemblies. Field-adjustable restricting mechanism reduces water pressure under flowing conditions (175 PSI max. inlet). When full flow is required, restriction can be over-ridden by trained personnel. Female NPT inlet and outlet, 175 PSI, cast brass, UL listed/FM Approved.

Model No.	Size	A	B (Open)	С	D	Swing Radius
5040	1½" x 1½"	4"	8"	21/2"	2"	2½"
5045	2½" x 2½"	5½"	11½"	31/2"	21/2"	3½"

Optional Finish: -B Polished Brass -C Rough Chrome Plated -D Polished Chrome Plated

Caps with Chains - Caps with Chains - Used to protect hose thread outlets on valves and hydrants.

Cast brass caps (pin lugs)* or red plastic caps (rocker lugs).

Model No.	Size	Туре
5515	1½"	Brass
☐ 5515P	1½"	Plastic
5 525	21/2"	Brass
☐ 5525P	21/2"	Plastic

Threads:

NST
Other



Reducer - Used to change outlet size. Rigid pin lug*, female x male threads.

Model No.	Size	Th			
3315	2½" x 1½"	▎╘			
Optional Finish:					

Optional Finish:

□-B Polished Brass□-C Rough Chrome Plated□-D Polished Chrome Plated

*Optional: -RL Rocker lugs





Optional Finish: ☐ -B Polished Brass ☐ -C Rough Chrome Plated

☐-D Polished Chrome Plated

*Optional: -RL Rocker lugs





