





3AA ProPolymer® HAZ-LO® Safety Rated Flashlight

FL 1 STANDARD	3AA PROPOLYMER HAZ-LO
	120 LUMENS
	6h 30min
	237m
	14,000cd



- Material/Lens** Impact and chemical resistant Engineering Polymer resin; o-ring sealed and vented. Available in high visibility yellow, orange or black. Unbreakable polycarbonate lens with scratch resistant coating
- Dims/Weight** Length: 7.00 in. (17.78 cm); Body thickness: 1.05 in. (2.67 cm); Width: 1.50 in. (3.81 cm); Face cap diameter: 1.93 in. (4.90 cm) 7.5 oz (213 grams) with batteries (included with purchase)
- Light Source** C4® LED technology, shock-proof with a 50,000 hour lifetime. Smooth parabolic reflector produces a tight beam with optimum peripheral illumination. Regulated run time provides consistent performance throughout battery life
- Switch** Push-button tail switch. Sealed switch design protects it from corrosion caused by battery leakage
- Battery**
- 3 "AA" alkaline batteries reduce battery and recycling costs by 25%
 - Combination of visual and mechanical polarity protection ensures correct installation of batteries
 - Light designed to not power on if batteries are installed incorrectly
- Features**
- High-performance, anti-static, thermoplastic material resistant to chemicals and solvents
 - "Captured locking" set screw will not back out - prevents FOD (Foreign Object Debris)
 - Safety measure: Set screw helps to avoid batteries being changed out, or the housing inadvertently being opened in a hazardous environment
 - Set screw goes into a metal tray that evenly distributes pressure to protect the body from over-tightening of the set screw
 - One body electronic LED module mechanically attached to electronic assembly
 - IP64/IPX7 rated; dust-tight, waterproof to 1m for 30 minute
 - 3 meter impact resistance tested
 - Ergonomically designed for maximum hand comfort
- Approvals** C-UL-US Classified Class I, Division 1, Groups A,B,C,D; Class II, Division 1, Groups E,F,G; Class III; Exia; Temperature Code T4
DEMKO 13 ATEX 1214468X II 1G Ex ia IIC T4 Ga (Zone 0) [excludes black model]
Most models meet applicable European Community Directives
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.



Item	UPC	Part #
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Yellow	080926-68720-2	68720
3AA ProPolymer HAZ-LO with alkaline batteries - Box - Yellow	080926-68723-3	68723
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Black	080926-68721-9	68721
3AA ProPolymer HAZ-LO with alkaline batteries - Box - Black	080926-68724-0	68724
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Orange	080926-68722-6	68722



Adheres to side of hard hat



Clips onto hard hats



Helmet Strap.
Helmet and light not included.

Poly Mount Kit - universal mounting via MSA V-Gard slot or self-adhesive mount

Includes straps for mounting the 4AA ProPolymax/3AA ProPolymer HAZ-LO, 2AA ProPolymer® Series or the PolyTac® LED Series

Item	UPC	Part #
4AA/3AA helmet mount	080926-68085-2	68085
4AA/3AA Gallet mount <i>(not shown)</i>	080926-68086-9	68086
Nylon Holster	080926-68905-3	68905
Poly Mount	080926-68089-0	68089
Rubber Helmet Strap	080926-99075-3	99075
3AA/4AA ProPolymer Series Belt Clip	080926-68088-3	68088
Lanyard with Push Button Slide <i>(not shown)</i>	080926-72024-4	72024



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
www.streamlight.com ©Streamlight, Inc. 3AA ProPolymer HAZ-LO 3/14