

ABC POWDER



Multi-purpose ABC Powder is a truly versatile extinguishant which is used to extinguish class.

A (carbonaceous) fires achieved by sealing the burning embers.

It is also used on class B (flammable liquid) fires.

Class C (flammable gas) fires under TS EN 3 and Electrical.

The 1 kg and 2 kg extinguishers are available stored pressure and 2 kg extinguishers with gas Cartridge.

ABC POWDER

| | | | |
|-----------------------------|---|-----------------|----------------|
| EXTINGUISHER CODA | ATK2 | ATIB1 | ATIB2 |
| PROPELLANT TYPE | 45gm | Stored Pressure | |
| | Co ₂ Gas Cartridge | | |
| CHEMICAL EXTINGUISHANT | ABC Dry Powder Mono, Ammonium Phosphate EN615 ISO7202 | | |
| CAPACITY | 2kg | 1kg | 2kg |
| PAINT PRIMER/FINISH | Iron Phosphate/Polyester | | |
| PAINT COLOUR | Body Red (RAL 3020) | | |
| FIRE CLASS | A - B - C Types + Electrical | | |
| FIRE RATING | 5A / 43B/C | 3A / 34B/C | 5A / 43B/C |
| OPERATING TEMP. | - 20° C to + 60° C | | |
| TEST PRESSURE | 30 Bar | | |
| OPERATING PRESS. AT. 20° C | 12 Bar | | |
| MIN. DISCHARGE TIME | 14 Secs | 7 Secs | 14 Secs |
| DISCHARGE RANGE | 3 metres | | |
| SAFE OPERATING DISTANCE | 2 metres | | |
| CYLINDER | 2.00 mm Mild Steel Grade CCRS 6114 | | |
| OPERATING VALVE | Diecast ZA5 Zinc Alloy BS 1004 | | |
| HEIGHT | 355 mm | 300 mm | 355 mm |
| DIAMETER | 116 mm | 90 mm | 116 mm |
| FULL | 4.180 kg | 2.750 kg | 4.180 kg |
| EMPTY (Excluding cartridge) | 1.820 kg | 1.150 kg | 1.820 kg |
| CARTON SIZE | 125x125x 360mm | 95x95x 300mm | 125x125x 360mm |
| * = APPROVED TO TS EN 3 | * | * | * |

ABC POWDER



K-Q
TS - EN - ISO
9002