

WA- TLF 3200/150 UBHEJANE

Forest Fire Fighting Vehicle



Basic specification

- **Chassis**
 - Type: MAN TGM 13.280 4x4 BB
 - Engine: Euro 3
 - Engine Output: 206 kW (280 HP)
 - Gearbox: Manual
 - Tyres: 365/80 R 20
 - Wheelbase: 3,650 mm
- **Superstructure and cabin**
 - Crew: 1 + 5
 - Cab / Crew Cab: > Original MAN Crew Cab
 - Superstructure: > The structure is made of steel profile tubes, fastened on a frame. The frame itself is mounted torsion free onto the chassis, by means of a 3-point suspension system. The panels are made of corrosion proof light alloy or polished stainless steel plates. All steel profile tubes are welded and screwed together, sandblasted and painted according internal Rosenbauer standards.
- **Water tank capacity** 3,200 litres
- **Foam tank capacity** 150 litres
- **Extinguishing system**
 - Type: > NH 20 normal and high pressure pump
 - Extinguishing output: > up to 2,000 l/min at 10 bar
> up to 400 l/min at 40 bar
 - Foam systems: > Rosenbauer FIXMIX (RTP)
 - Quick attack: > reel with 55 m hose with fog nozzle NEPIRO Ergo
- **Additional features:**
 - Self-protection noddles for cab, superstructure and tyres
 - RAMSEY RE 12000, front mounted electric winch

Measurements and weights

L x W x H	7,200 x 2,500 x 3,150 mm
Dead weight	ca. 8,700 kg
GVW	13,000 kg

Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-DW/Ext
Fax: +43 732 6794-DW/Ext
office@rosenbauer.com

www.rosenbauer.com