

ATTACK 100C, 500C & 750C

CONSTANT FLOW NOZZLES



Attack 100C
1" BSP Female



Attack 750C
Inlet: Storz C



Attack 500C
Inlet: 2" BSP Male

- Stainless Steel Spinning Teeth
- Long Range Penetrating Jet
- Dense Wide Angle Fog Pattern
- Constant Fixed Flow Rates
- Colours Options Available
- Easily Maintained
- 30% Lighter than Most Comparable Branches



Stainless Steel Spinning Turbine Teeth

NOZZLES / BRANCHES

GENERAL DESCRIPTION

The Delta Attack 100C, 500C and 750C represents the state of the art nozzle design, providing a powerful, long range main jet with a coherent stream pattern, combined with high performance water spray patterns.

The computer designed waterway maximises hydraulic efficiency and combines it with the lightest most compact design in its class.

FEATURES

CONSTANT FIXED FLOW RANGE (AT 6 BAR)

Attack 100C = 75 or, 100 or 125 L/Min (Alternative Fixed Flows Available)

Attack 500C = 125 or 250 or 375 or & 500 L/Min

Attack 750C = 285 or 460 or 600 or 750 L/Min

Cohesive jet and dense water spray pattern at one of the above flow setting.

Normal operating range 5 to 8 bar, but fully operational at pressures as low as 3.5 bar

POWERFUL FOG PATTERN - STAINLESS STEEL SPINNING TEETH

Computer designed stainless steel turbine spinning teeth produce an extremely dense fog pattern, giving excellent fire fighting capability and higher degrees of personal protection. Plastic teeth are available as a lower cost option.

NARROW ANGLE CLICK SETTING

The nozzle jet / spray pattern has a single narrow angle click position, which is positive enough to hold the setting in operational use and is easily identifiable in 'blind' fire scenarios.

LOW MAINTENANCE AND RUGGED CONSTRUCTION

The stainless steel ball valve design means only minimal maintenance. An optional stainless steel mesh filter and wide flush setting stop any obstruction of the water flow in use.

TEN YEAR GUARANTEE

Designed and manufactured in the United Kingdom under an ISO 9001 Quality System. Every Delta Attack nozzle is subjected to rigorous quality controls and guaranteed against any manufacturing defect for ten years.

SPECIFICATION

Model Ref	Description
A100C-19	Nozzle With ¾" or 1"
A100C-25	BSP Female Swivel Inlet
A500C-65	Nozzle With 2½" Male Instantaneous Swivel Inlet
A750C-65	Nozzle With 2½" Male Instantaneous Swivel Inlet

A100C-25 230mm (max overall)

A500C-65 325mm (max overall)

A750C-65 340mm (max overall)

Weight: Attack 100C - 1.6kg
Attack 500C - 1.8kg
Attack 750C - 2.4kg

Main Body/Barrel: Hard Anodised Aluminum

Ball Valve: Stainless Steel

Front Bumper: Shockproof Polyurethane

