



# SPECIFICATION SHEET

## R3T KIWI™

### PACIFIC R3T KIWI USAR™ RESCUE HELMET

- Compliant with ANSI Z89.1
- Light holder accommodates optional UK torch light with 4 AA batteries
- Lightweight Dupont™ Kevlar® composite shell weighs less than composite fiberglass and composite alternatives
- Shell is not affected by UV exposure
- Composite resins offer higher temperature resistance (up to 600°F) without distorting or melting
- Ratchet headband with easy-to-adjust dial which accommodates a variety of head sizes (52-64cm)
- 3-point polyester chin strap comes with quick release buckle
- Neck protector (optional) for ear and neck protection
- Full range of tailored Decals/Badges/Reflectorising available
- ESS mounts make goggle attachment quick and easy, even with gloves on
- Face shield protects against hazards and blood borne pathogens (optional)

### APPLICATIONS

- Collapse Rescue
- Auto Extrication
- Technical rescue

### TECHNICAL DATA

|             |  |
|-------------|--|
| MATERIAL    | Outer Shell: Kevlar® composite / Inner Shell: Polyurethane   |
| SUSPENSION  | Pacific mesh ribbon cradle   |
| COLOR       | <input checked="" type="checkbox"/> Yellow (806-3011)<br><input checked="" type="checkbox"/> Red (806-3010)<br><input type="checkbox"/> White (806-3009) |
| SIZES       | OSFA, Adjustable   |
| PACKAGING   | 10 per case  |
| CASE        | 26.5" x 23.5" x 13" / 67.3cm x 59.6cm x 33.0cm   |
| CASE WEIGHT | 25.0 lbs / 11.34 kg  |
| COO         | New Zealand  |
| HARM CODE   | 6506.10.6075   |

### WARRANTY

6-year limited warranty

Each helmet also carries a 2-year limited warranty on impact liners and ratchet suspensions. Internal parts including crown pads, ribbons and sweatbands are NOT covered by this warranty.

### BARCODES

| ITEM   | EACH         | DOZEN | CASE           |
|--|--------------|-------|----------------|
| <input checked="" type="checkbox"/> 806-3011 | 616314149399 | ---   | 02616314149397 |
| <input checked="" type="checkbox"/> 806-3010 | 616314149580 | ---   | 02616314149588 |
| <input type="checkbox"/> 806-3009            | 616314149795 | ---   | 02616314149793 |



### DIMENSIONS (in/cm)

|          | OSFA        |  |  |  |  |
|----------|-------------|--|--|--|--|
| <b>A</b> | 9.5 / 24.1  |  |  |  |  |
| <b>B</b> | 12.0 / 30.5 |  |  |  |  |

