




MODEL V-7041 FLANGE ANSI CLASS 125/150

VGS Model V-7041 flange adapters 2" through 12" (50mm ~ 300mm) are supplied hinged as a single assembly. Maximum working pressure is up to 300 psi (20 bar).



2" - 12" (hinged)



Nominal Size mm/in	Pipe O.D. mm/in	Max. Working Pressure Bar/PSI	Max. End Load kN/Lbs	Dimensions			Sealing Surface		Bolt		Weight Kgs/Lbs
				A mm/in	B mm/in	C mm/in	D mm/in	E mm/in	Size mm/in	No.	
50	60.3	20	5.7	152	121	19	60	87	---	4	2.0
2	2.375	300	1330	6.00	4.75	0.75	2.36	3.42	5/8	4	4.4
65	73.0	20	8.4	178	140	22	73	102	---	4	2.5
2.5	2.875	300	1950	7.00	5.50	0.87	2.87	4.00	5/8	4	5.5
80	88.9	20	12.3	190	152	24	89	116	---	4	3.4
3	3.500	300	2890	7.50	6.00	0.94	3.50	4.56	5/8	4	7.5
100	114.3	20	20.5	229	191	24	114	141	---	8	4.0
4	4.500	300	4770	9.00	7.50	0.94	4.50	5.56	5/8	8	8.8
150	168.3	20	44.5	279	241	25	168	198	---	8	5.5
6	6.625	300	10340	11.00	9.50	1.00	6.62	7.79	3/4	8	12.1
200	219.1	20	75.3	343	298	28	219	254	---	8	8.0
8	8.625	300	17520	13.50	11.75	1.12	8.62	10.00	3/4	8	17.6
250	273.0	20	117.0	405	355	26	273	308	---	12	11.7
10	10.750	300	27210	16.00	14.25	1.18	10.75	12.12	7/8	12	25.7
300	323.9	20	164.7	460	410	28	324	359	---	12	17.7
12	12.750	300	38280	19.00	17.00	1.25	12.75	14.13	7/8	12	38.9

* Also available with hot dip zinc galvanized finished (optional).