

Specialty Nozzles

Brass Fog Nozzles

A combination fog and straight stream nozzle designed for efficiency with foam or water on offshore rigs and in industrial applications.

- Molded teeth
- Rubber-like bumper and handle
- Constant gallonage in fog and straight stream patterns
- Flush without shutting down
- Repair kits available
- Style 775 Quick Attack™ Foam Tube for Styles 3015-3021

Style	Inlet	Length	Weight lbs. (kg)	Flow At 100 Psi		Pistol Grip
				GPM	LPM	
3015	1 1/2" (3.8 cm)	8 5/8" (21.9 cm)	7 1/8 (3.2 kg)	95	360	-
3016	1 1/2" (3.8 cm)	8 5/8" (21.9 cm)	7 1/8 (3.2 kg)	125	475	-
3019	1 1/2" (3.8 cm)	8 5/8" (21.9 cm)	7 3/4 (3.5 kg)	95	360	YES
3021	1 1/2" (3.8 cm)	8 5/8" (21.9 cm)	7 3/4 (3.5 kg)	125	475	YES
3025	2 1/2" (6.4 cm)	10" (25.4 cm)	13 (5.9 kg)	250	950	-



Style 3019

Cellar Nozzles

- For attacking fires in hard-to-reach places
- Ball bearing revolving action

- 535 2 1/2" Cellar Nozzle**
- 9 variable angle orifices: (3) 1/4" and (6) 13/32"
 - Meets Insurance Services Office (ISO) requirements
- 536 1 1/2" Cellar Nozzle**
- 6 variable angle orifices: (3) 1/4" and (3) 5/16"

Style 536



Style	Inlet	Length	Weight lbs. (kg)	Flow at 100 PSI	
				GPM	LPM
535	2 1/2" (6.4 cm)	5 1/8" (13.0 cm)	4 1/2 (2.0 kg)	250	950
536	1 1/2" (3.8 cm)	3 1/2" (8.9 cm)	4 1/4 (1.9 kg)	* 95	* 360

* At 50 psi

Piercing Applicator

Use a sledge hammer to drive the Piercing Applicator through concrete block, cars, mobile homes, etc. It's designed to get water or foam into hidden trouble spots. The driving button and point are made of hardened tool steel with impinging jets for a dense fog pattern. Plus it's compatible with Class A and B foams.

- 1088 Piercing Applicator**
- Specify 3' or 6' length

- PA-3D Piercing Applicator Extension**
- 3 ft. extension PA-3D is designed to screw into the end of the piercing applicator (Style 1088) in place of the drive button providing extra reach. This New Piercing Applicator Extension allows extra vantage for those hard to reach areas.

- 3 ft. extension to your Akron Piercing Applicator
- Easy to control D-Ring Handle
- Heavy Duty, Lightweight, 1 1/4" Fiberglass Pole
- Durable threaded connection



Style	Inlet	Length	Weight lbs. (kg)	Flow at 100 PSI	
				GPM	LPM
1088	1 1/2" (3.8 cm)	3' (91.4 cm)	11 (5.0 kg)	125	475



Piercing Applicator Extension

Pistol Grip Adapter

- 1719 Pistol Grip Adapter**
- Pyrolite® finish
 - 1 1/2" swivel inlet x 1 1/2" outlet
 - Length: 5 7/8"
 - Weight: 1 3/4 lbs.



1.5" Thread Protector

- 2400 Thread Protector**
- The thread protector is designed to protect the threads on products like the Saber™ Shutoff, Leader Line Wyes, Mini Stream Shapers, In-Line Eductors or anything with 1.5" threads. This 1.5" thread protector comes with a sure grip knurled finish that makes it easy to affix and/or remove. It is made of orange anodized aluminum.



1" Self-Educting Forestry Nozzle

- 1230 1" Self-Educting Forestry Nozzle**
- Heavy Duty Pyrolite Construction
 - Self-Educting for ease of use with agent application
 - Dual shutoff for better performance
 - Bail shutoff to stop the water flow
 - Twist shutoff to allow back flush
 - Eductor back-flush for easy cleaning of agents out of the eductor
 - Check valve in Eductor to prevents water from entering the agent
 - Static mixer in throat for better gel mixing for better performance
 - Variable pattern control for straight stream to fog pattern
 - 15 GPM at 100 psi: Ideal setting for gel applications



Style 1230

Forestry/Wildland Nozzles

Small lightweight nozzles designed for the rugged simplicity needed for forestry/wildland applications

- 1030 Forestry Nozzle**
- A dual flow adjustable pattern nozzle with a simple twist operation allows you to switch from Off, to low flow straight stream, to low flow narrow fog, to high flow straight stream, to high flow fog.



Style 1030



Style 1700

- 1700 Bush Nozzle**
- A three flow setting adjustable pattern nozzle with the flow control and off settings
 - Easy to operate control ring
 - Adjustable pattern from straight stream to fog at any flow.
 - Quarter turn, quick action pattern change
 - 10 year warranty
 - NFPA compliant
 - Maximum operating pressure 250 psi

Style	Inlet	Length	Weight lbs. (kg)	Flow at 100 PSI	
				GPM	LPM
1030	1" (2.4 cm)	4" (10.2 cm)	1/2 (.2 kg)	30-Oct	38 -115
1700	1" (2.4 cm)	6 3/8" (15.3 cm)	2 (.9 kg)	Mop (8)-15-30	30-60-115

Hose Rack Nozzle

- 721 Hose Rack Nozzle**
- 1 1/2" FM approved
 - Shuts off past wide fog to reduce reaction force when opening
 - Available in cast or chrome finish

Style	Inlet	Length	Weight lbs. (kg)	Flow at 100 PSI	
				GPM	LPM
721	1" (2.4 cm)	4 3/4" (12.0 cm)	2 1/2 (1.1 kg)	34	128
721	1 1/2" (3.8 cm)	5 3/4" (14.6 cm)	4 5/8 (2.1 kg)	115	435



Industrial Fog Nozzle

- 1300 1 1/2" Industrial Fog Nozzle**
- Shuts off past straight stream and fog pattern
 - Cast finish only

Style	Inlet	Length	Weight lbs. (kg)	Flow at 100 PSI	
				GPM	LPM
1300	1 1/2" (3.8 cm)	5 5/8" (14.3 cm)	4 1/4 (1.9 kg)	128	485



Fog Applicator

- 2055 Fog Applicator**
- Designed for those hard-to-reach areas such as tank cars.
 - Compatible with Class A and Class B foams (Not recommended for foam requiring air-aspiration, i.e. protein and alcohol types)
 - Lightweight aluminum tubing
 - Includes Style 1048: 2 1/2" Coast Guard Fog Head.
 - Specify length



Available in the following lengths:

- 4' with 60° Bend
- 6' with 90° Bend
- 10' with 90° Bend

Style	Inlet	Length	Weight lbs. (kg)	Flow at 100 PSI	
				GPM	LPM
2055	1 1/2" (3.8 cm)	10' (304.8 cm)	6 1/2 (7.5 kg)	95	360