

Horns

Vibrating

870 Series

The 870 Series flush mount vibrating horns are low-current, high decibel for heavy-duty indoor use. Designed for wall or panel installation and projects less than 1" (25mm) from the mounting surface. A trim plate is included and a back box is required.



Features and Specifications

- Corrosion resistant finish
- Volume adjustable
- Completely assembled
- Heavy duty die-cast housing
- Operating voltage range: -20% to +10% of nominal voltage

870 AC

- Adjustable output: 88 to 113dB @ 1m (78 to 103dB @ 10ft.)

871 DC

- Adjustable output: 88 to 101dB @ 1m (78 to 91dB @ 10ft.)

Ordering Information

Description	Cat. No.	Operating Voltage ²	Current	VA	dB at 1m/10ft. ¹	DC Coil Res (Ohms)
Flush Mount AC	870-G5	24V AC	0.63 A	15.1	113/103	5.2
	870-N5³	120V AC	0.13 A	15.6	113/103	150
	870-R5	240V AC	0.07 A	16.8	113/103	580
Flush Mount DC	871-E1	12V DC	0.27 A	3.2	111/101	6.0
	871-G1	24V DC	0.16 A	3.8	111/101	24
	871-K1	48V DC	0.07 A	3.4	111/101	96
	871-P1	125V DC	0.025 A	3.1	111/101	600
	871-S1	250V DC	0.014 A	3.5	111/101	2640

¹dB rating measured in anechoic chamber.

²AC voltage frequency is 50/60 Hz.

³Diode Polarized version available in red, order **880D-N5**.

Accessories

Description	Cat. No.
Wall Box	870-B
Plastic Projector	872-PO

Signal Input Load Characteristics

These devices may be operated by PLCs with output characteristics that match the input load requirements of the signal.

Cat. No.	Operating Voltage	Max. Off State Leakage Current (A)	Continuous On Current (A)	Surge (Inrush/Duration) Amps/Seconds
870-N5	120V AC @ 60 Hz	0.025	0.120	1.02/.000026
871-G1	24V DC	0.025	0.150	1.7/.000042



Horns Vibrating 870 Series

Weights and Dimensions

Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
870-G5	2.06	2.30
870-N5	2.06	2.30
870-R5	2.06	2.30
871-E1	2.06	2.30
871-G1	2.06	2.30
871-K1	2.06	2.30
871-P1	2.06	2.30
871-S1	2.06	2.30
870-B	1.26	1.28
872-PO	0.34	0.58

