

TLF 3300 / 200

Forest Fire Fighting Vehicle



Rosenbauer Española, Spanien



Basic specifications

Chassis

- Type: Unimog U5000 / 38 CD
- Engine: OM 924 LA
- Engine output: 218 hp / 170 kW
- Exhaust gas standard: Euro 4
- Gearbox: MB UG 100, 8 forward, 6 reverse gears

Superstructure and cabin

- Crew: 1 + 5
- Driver's cab: MB crew cabin
- Superstructure: two-module, with formed, aluminum tubular ribs and aluminum sheets

Extinguishing agents (usable content) / tank material

- Water: 3,300 l / GRP
- Foam: 200 l / GRP

Extinguishing systems

- Pump: Rosenbauer NH30
- Output: 3,000 l/min at 10 bar
400 l/min at 40 bar
- Quick attack: reel with 30 m hose

Additional features

- Self-protection nozzles for cab, superstructure and tires
- WARN, front-mounted, electric winch
- 3.5 t towing hook
- Fire-protected cabling in the frame

L x W x H	6,600 x 2,490 x 3,280 mm
GVW	13,100 kg

Contact

Rosenbauer International Aktiengesellschaft
Paschinger Straße 90
4060 Leonding, Austria
Phone: +43 732 6794 - 0
Fax: +43 732 6794 - 77

www.rosenbauer.com