


Grooved Flange Adaptor

321GL-PN10


Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut No.-Size mm	Certificate
			L mm/in	X mm	Y mm	Z mm		
200 8	219.1 8.625	145 1.0	80 3.150	340 13.39	295 11.61	19 0.75	8-M20	UL FM
250 10	273.0 10.750	145 1.0	85 3.346	405 15.94	350 13.78	21 0.83	12-M20	UL FM
300 12	323.9 12.750	145 1.0	90 3.543	460 18.11	400 15.75	24 0.94	12-M20	UL FM

321G-PN16


Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut No.-Size mm	Certificate
			L mm/in	X mm	Y mm	Z mm		
25 1	33.7 1.327	225 1.6	60.5 2.382	115 4.53	80 3.15	16 0.63	4-M12	UL FM VdS
32 1¼	42.4 1.669	225 1.6	60.5 2.382	140 5.51	100 3.94	16 0.63	4-M16	UL FM VdS
40 1½	48.3 1.902	225 1.6	60.5 2.382	150 6.91	110 4.33	16 0.63	4-M16	UL FM VdS
50 2	60.3 2.375	225 1.6	65 2.559	165 6.50	125 4.92	16 0.63	4-M16	UL FM VdS
65 2½	76.1 3.000	225 1.6	65 2.559	185 7.28	145 5.70	16 0.63	4-M16	UL FM VdS
80 3	88.9 3.500	225 1.6	65 2.559	200 7.87	160 6.30	16 0.63	8-M16	UL FM VdS
100 4	108.0 4.250	225 1.6	70 2.756	220 8.66	180 7.09	16 0.63	8-M16	UL FM
100 4	114.3 4.500	225 1.6	70 2.756	220 8.66	180 7.09	16 0.63	8-M16	UL FM VdS
125 5	133.0 5.250	225 1.6	70 2.756	250 9.84	210 8.27	18 0.71	8-M16	UL FM
125 5	139.7 5.500	225 1.6	70 2.756	250 9.84	210 8.27	18 0.71	8-M16	UL FM VdS
150 6	159.0 6.250	225 1.6	70 2.756	285 11.22	240 9.45	18 0.71	8-M20	UL FM
150 6	165.1 6.500	225 1.6	70 2.756	285 11.22	240 9.45	18 0.71	8-M20	UL FM
150 6	168.3 6.625	225 1.6	70 2.756	285 11.22	240 9.45	18 0.71	8-M20	UL FM VdS
200 8	219.1 8.625	225 1.6	80 3.150	340 13.39	295 11.61	19 0.75	12-M20	UL FM VdS
250 10	273.0 10.750	225 1.6	85 3.346	405 15.94	355 13.98	21 0.83	12-M24	UL FM VdS
300 12	323.9 12.750	225 1.6	90 3.543	460 18.11	410 16.14	24 0.94	12-M24	UL FM VdS
350 14	377.0 12.843	225 1.6	100 3.937	520 20.47	470 18.50	25 1.00	16-M24	UL FM
400 16	426.0 16.772	225 1.6	110 4.331	580 22.83	525 20.67	27 1.06	16-M27	UL FM

321GH-PN25

Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut No.-Size mm	Certificate
			L mm/in	X mm	Y mm	Z mm		
100 4	108.0 4.250	362 2.5	70 2.756	230 9.05	190 7.48	18 0.71	8-M20	UL FM
100 4	114.3 4.500	362 2.5	70 2.756	235 9.25	190 7.48	16 0.63	8-M20	UL FM
150 6	159.0 6.250	362 2.5	70 2.756	300 11.80	250 9.85	20 0.79	8-M24	UL FM
150 6	165.1 6.500	362 2.5	70 2.756	300 11.80	250 9.84	18 0.71	8-M24	UL FM
200 8	219.1 8.625	362 2.5	80 3.150	360 14.17	310 12.20	19 0.75	12-M24	UL FM



Rapidrop Global


Rutland Business Park, Newark Road, Peterborough, PE1 5WA, United Kingdom
 Tel: +44 (0) 1733 847 510 Fax: +44 (0) 1733 553 958
 e-mail: rapidrop@rapidrop.com web: www.rapidrop.com

Continued overleaf
 Page 1 of 2

Grooved Flange Adaptor

321GA-ANSI 125/150

Class 125/150
Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut	Certificate
			L mm/in	X mm	Y mm	Z mm	No.-Size mm	
50 2	60.3 2.375	300 2.07	65 2.559	165 6.50	120.7 4.75	16 0.63	4-5/8	UL FM
65 2½	73.0 2.875	300 2.07	65 2.559	185 7.28	139.7 5.50	16 0.63	4-5/8	UL FM
80 3	88.9 3.500	300 2.07	65 2.559	200 7.87	152.4 6.00	16 0.63	8-5/8	UL FM
100 4	114.3 4.500	300 2.07	70 2.756	229 9.01	190.5 7.50	16 0.63	8-5/8	UL FM
150 6	168.3 6.625	300 2.07	70 2.756	282 11.10	241.3 9.50	18 0.71	8-3/4	UL FM
200 8	219.1 8.625	300 2.07	80 3.150	340 13.39	298.5 11.75	19 0.75	8-3/4	UL FM

321GJ

JIS 10K
Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut
			L mm/in	X mm	Y mm	Z mm	No.-Size mm
65 2½	76.3 3.00	10	65 2.559	175 6.89	140 5.51	18 0.71	4-M16
80 3	89.1 3.50	10	65 2.559	185 7.28	150 5.91	18 0.71	8-M16
100 4	114.3 4.50	10	70 2.756	210 8.27	175 6.89	18 0.71	8-M16
125 5	139.8 5.50	10	70 2.756	250 9.84	210 8.27	20 0.79	8-M20
150 6	165.2 6.50	10	70 2.756	280 11.02	240 9.45	20 0.79	8-M20

321G-BS. TABLE 'E'

Adaptor Flange



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Dimensions				Bolt/Nut
			L mm/in	X mm	Y mm	Z mm	No.-Size mm
65 2½	76.1 3.000	225 1.6	70 2.756	165 6.50	127 5.00	16 0.63	4-M16
80 3	88.9 3.500	225 1.6	70 2.756	184 7.24	146 5.75	16 0.63	4-M16
100 4	114.3 4.500	225 1.6	70 2.756	216 8.50	178 7.00	16 0.63	8-M16
150 6	165.1 6.500	225 1.6	70 2.756	280 11.02	235 9.25	21 0.71	8-M20
200 8	219.1 8.625	225 1.6	102 4.02	337 13.27	292 11.50	19 0.75	12-M20



Rapidrop Global

Rutland Business Park, Newark Road, Peterborough, PE1 5WA, United Kingdom
Tel: +44 (0) 1733 847 510 Fax: +44 (0) 1733 553 958
e-mail: rapidrop@rapidrop.com web: www.rapidrop.com