

FIRE HOSE STORAGE RACKS

- ◆ For clear, stationary storage of suction and pressure hoses of size A - C
- ◆ Mixture of basic and extension units allows extension as required
- ◆ 3 possible shelf heights allow optimal utilization of available storage space

Fittings:

- ◆ All shelving parts galvanized
- ◆ Screwless plug-in installation
- ◆ Storage levels height-adjustable at intervals of 25 mm
- ◆ Max. load per storage level 100 kg with uniformly distributed load
- ◆ Max. unit load 500 kg
- ◆ Hose storage level with integrated liquid channel
- ◆ With optional top shelf for the storage of different goods
- ◆ Dismounted delivery for easy self-assembly



FW-SLR 2000, Article No. R71-5001-A, basic unit and FW-SLR 2000, Article No. R71-5002-A, extension unit



FW-SLR 2000, basic unit, Article No. R71-5001-A and FW-SLR 2000, extension unit, Article No. R71-5002-A, with optional top shelf



Shelving systems for hazardous substances can be found on page 54!



FW-SLR 2200, Article No. R71-5003, with optional top shelf

Model	FW-SLR 2000	FW-SLR 2200	FW-SLR 2500
External dimensions, basic unit W x D x H (mm)	1060 x 535 x 2000	1060 x 535 x 2200	1060 x 535 x 2500
Numbers of storage levels with liquid channel	3	3	4
Article No., basic unit	R71-5001-A	R71-5003-A	R71-5005-A
External dimensions, extension unit W x D x H (mm)	1010 x 535 x 2000	1010 x 535 x 2200	1010 x 535 x 2500
Article No., extension unit	R71-5002-A	R71-5004-A	R71-5006-A

Accessories	Article No.
Additional storage level with integrated liquid channel	R71-5007-A
Top shelf	R71-5008-A

FIRE HOSE STORAGE CARTS

- ◆ For clearly, mobile storage and transport of suction and pressure hoses of size A - C
- ◆ Ideally suited for loading and unloading of a fire department tank pumper

Fittings:

- ◆ All shelving parts galvanized
- ◆ Screwless plug-in installation
- ◆ Storage levels height-adjustable at intervals of 25 mm
- ◆ Max. load per storage level 100 kg with uniformly distributed load
- ◆ Max. unit load 300 kg
- ◆ Hose storage level with integrated liquid channel
- ◆ With two swiveling and two fixed castors
- ◆ Dismounted delivery for easy self-assembly



Model	FW-SLW 1600
External dimensions W x D x H (mm)	1060 x 535 x 1600
Numbers of storage levels with integrated liquid channel	3
Article No.	R71-5009-A

FW-SLW 1600, Article No. R71-5009-A

