



# G-Force Multiflo 500

G- Force Nozzles: simplicity & safety

---

## Variable Flow nozzle – 500 l/min 3 selectable flows

- Large ring for flow-rate selection: 100 , 250 , 500 l/min & Flush
- Wide flow handle easily manoeuvrable for instant reaction
- Powerful full cone spray for smothering flames.
- Flush during operation on selector ring.
- Unbreakable teeth; Maintenance unnecessary.
- Hard anodised aluminium.
- Strainer to prevent large debris ingress.
- Compliant with EN15182-2 type 3.
- Patent Pending



- Can be upgraded to become an automatic nozzle type 4
- 3 selectable flows
- Slide valve for keeping perfect stream quality
- Shock absorber in the bumper



Grips available in several colours

## G-Force: Mach3 & Quadrafog advantages combined in the Multiflo 500 :

### - Mach3 Automatic Advantages:

- Mach3 quality :vulcanized bumper, hard anodized aluminium ...
- Slide valve for instant reflex
- Strainer

### - Quadrafog Advantages:

- Selectable flow-rates 100, 250, 500 l/min
- Flush on selector ring
- Stream quality and fog pattern




### Innovations:

- Shock absorber
- Spray pattern removable lock (optional)
- Easy customization
- New Foam adaptor fixing



### Flow / Pressure curves - Multiflo 500 @ 6 bar:



### REDUCED COST OF OWNERSHIP:

Very light maintenance requirement due to the nozzle design and materials used.



Multiflo-ZF01.130.EN.1

As it is our policy to constantly seek to improve our products, we reserve the right to change the specification of our equipment without notice