



Petrol driven ventilator MT280

Easy Pow'Air Technology

Positioning from 0.90 m to 6 m

- **Automatic tilt:** Lifting the handle tilts the ventilator automatically to the correct working position.
- **Positioning between 0,90 m and 6m :**
 - Effective between 2 to 6 m from the opening
 - Can also be positioned as near as 0,90 m
- **Air Flow: 85 200 m³/h**
- **Stable & Easy to handle:** With its large wheels at the back, the MT280 is very easy to handle even in very adverse terrain.
- **Strengthened turbine.**
- **Protective Frame:** epoxy coating.
- **Noise:** 99 dBA at 3m (positioning the ventilator at a further distance reduces the noise level for the user).
- **Can be positioned to the precise angle you need** between +10° and +20°
Tilt positioning accessory to ventilate sub-terrain levels.
The angle above 10° together with allowed distance negates problems with stair landings.



- **Air Flow: 85 200 m³/h**
- **Easy to handle: automatic tilt**



CHARACTERISTICS

Model	Reference	Engine	Running time At full speed (working inclination)	Dimensions W x H x D	Weight
MT280	I60.10.048	13 HP HONDA - GX 390 - 4 stroke	1H20	72 x 78 x 62	69 kg

ACCESSORIES


5m Duct	I60.20.113	Exhaust Pipe Extension – length 2.5m	I60.20.012
Mister Adaptor	I60.20.104	Protective Cover	I60.20.097
High Expansion Foam Adaptor	I60.20.116	-10° Tilt Positioning Adaptor	I60.20.108
Exhaust Pipe Adaptor Hour meter	I60.20.125	Hour meter	I60.20.135



Easy Pow'Air Technology added to the Turbo-ventilators' specific air entrainment effect:


Advantage 1:

Effective between 2 to 6 m.
Can also be positioned as near as 0,90 m



Advantage 2:

Easy to handle:
More space between the entrance and the ventilator.



Advantage 3:

Ventilate in all circumstances,
even with raised floors or steps

Advantage 4:

Reduced noise level for users due to a
positioning further away from the entrance.

MAINTENANCE :

Reduced maintenance due to its robust conception.
All the components are easily interchangeable by the user.



ZF03.113.EN.2

As it is our policy to constantly seek to improve our products, we reserve the right to change the specification of our equipment without notice