

Newtonian low viscosity alcoholresistant fluoroprotein FPAR foam concentrate for 3% application on hydrocarbon fires and 6% on polar liquid fires

Description

UNIVEX 3x6 Super is a totally new formulated universal foam for severe and diversified Marine applications. It is a superior alcohol resistant fluoroprotein foam concentrate (FPAR) for extinguishing flammable hydrocarbon and polar solvent liquid fires at 3% induction ratio on Hydrocarbon fires and at 6% induction ratio on Polar solvent and Alcohol fires.

UNIVEX 3x6 Super protein base provides highly stable foams with drainage times that do not suffer from extreme heat conditions in large tank fires. Unlike other alcohol resistant like ARAFFF foam concentrates, it has the fluidity and low viscosity of a regular protein foam concentrate.

UNIVEX 3x6 Super is the right choice for maximum safety and costeffectiveness for hydrocarbons and polar solvent fires.

Performance

UNIVEX 3x6 Super is measured against specifications and standards such as IMO circular 582 on Heptane and 799 on both Acetone and Isopropanol Polar Solvents. It meet also the additional DNV requirement on retention survey required for Alcohol resistant protein based foams.

When used with fresh or salt water or water at the correct dilution and with most conventional foam making equipment, the expansion ratio will vary depending on the performance characteristics of the equipment. Air aspirating discharge devices produce expansion ratios from 6:1 to 12:1 depending primarily on type and flow rate. In general, the higher the flow rate the higher the expansion ratio.

Typical expansion ratios for air aspirating foam nozzles are in the range of 5:1 to 7:1, and for foam water monitors in the range of 4:1 to 8:1.

Application

UNIVEX 3x6 Super ARFluoroprotein Foam Concentrate is intended for use on any Class B flammable liquids both on hydrocarbon fuels having low water solubility (crude oils, gasolines, diesel fuels, aviation fuels, etc.) and is also suitable for use on Polar solvent fuels having water solubility (Acetone, Isopropanol, MTBE, ...) at the appropriate concentration. This concentrate can be used only with air aspirating type discharge devices.

It can also be used with foam compatible dry chemical extinguishing agents without regard to the order of application, to provide even greater fire protection capability.

UNIVEX 3x6 Super can be used by most conventional foam equipment such as:

- Balance pressure pump proportioning equipment
- Bladder tank and related proportioners
- Aroundthepump proportioners
- Fixed and portable Inline venturi type inductors



Approvals

UNIVEX 3x6 Super is tested and approved according to:
IMO Msc Circ 582
IMO Msc Circ 799

Storage and shelf life

UNIVEX 3x6 Super has an operational temperature range of -10°C and $+60^{\circ}\text{C}$. Limited exposure to temperatures above $+60^{\circ}\text{C}$ does not affect the firefighting performance.

When stored in the packaging supplied (polyethylene drums or pails) within the temperature limits specified, or in equipment recommended by the manufacturer as part of the foam system, the shelf life of UNIVEX 3x6 Super Fluoroprotein Foam Concentrate is generally in excess of 10 years.

The factors affecting shelf life and stability for SABO Foam agents are discussed in detail in our Technical Bulletin for storage recommendation.

If the product is frozen during storage or transportation, the concentrate should be thawed and used without any de-generation of the performance.

Safety and handling

See our corresponding "Material Safety data sheet".

Compatibility

There are no specifications or standards which address the subject of compatibility of different manufacturer's brands of fluoroprotein alcohol resistant foam concentrates. In an emergency or if the manufacturer has supporting test data to substantiate that the mixture meets the same requirements as the individual component concentrates, they may be mixed together in the same storage vessel.

Different types of foam concentrates, i.e., AFFF and fluoro-protein base should not be mixed under any circumstances.

Quality insurance

UNIVEX 3x6 Super – as with all SABO Española Products – is subject to a very stringent quality controls throughout all stages of production, from incoming raw to the complete product and is manufactured in an ISO 9001:2000 controlled facility. Quality assurance is therefore guaranteed.

Typical properties

UNIVEX 3x6 Super	FP AR 3x6	
Fire Classes	B	
Shape and color	Brown, clear liquid	
Smell	Characteristic, protein	
Density (20°C)	1,12 ±0.02 [g/ml]	
pH (concentrate, 20°C / IMO 3.5)	7,0 ±0.5	
Viscosity 20°C (IMO 3.4)	8.0 ±4.0 [mm ² /s]	
Sediment (IMO 3.3)	≤ 0,25 [%]	
Admixing ratio	3 [% Vol.]	6 [% Vol.]
Expansion Ratio (IMO 3.7)	≥ 6,5	≥ 7,5
Drain Time 25%, (IMO 3.8)	≥ 4:30	≥ 7:00 [min:s]
Drain Time 50%, (IMO 3.8)	≥ 8:00	≥ 12:00 [min:s]
Expansion	Low, Medium	
Freezing Point	≤ -15 [°C]	
Pour Point	≤ -12 [°C]	
Recommended storage/Usage temperature	-10 to +60 [°C]	

Ordering information

UNIVEX 3x6 Super can be supplied in cans, drums, totes or Bulk (contact us for Bulk delivery).

Part No. F516355C2 20 Liter can Part
No. F516355C1 25 Liter can Part No.
F516355D1 200 Liter drum Part No.
F516355T1 1000 Liter tote